

Class 200 Polyester Film-Insulated Round Copper Magnet Wire

Table1 Specifications

Insulation materials	Polyester Film-Insulated; Polyester (Imide) Film-Insulated; Polyester (Amide) Film-Insulated
Dimensions	Single 14-56 AWG in accordance with 0.0165mm-1.692mm Heavy 4-50 AWG in accordance with 0.0356mm-5.329mm
Insulation thickness	Single and Heavy
Thermal Class	200
Certificate	MW 74-C



Table 2 Properties

Adherence and flexibility	No cracks visible in the film coating
Elongation	Not less than the value in 5-38
Heat shock	No cracks visible in the film coating after conditioning at 220°C
Springback	14-30 AWG: not greater than the value in 42-66 4-13 AWG: not greater than 5°
Dielectric breakdown	4-9.5 AWG: not less than the value in 3400v-3700v 10-37 AWG: not less than the value in 1220v-3170v 38-56 AWG: not less than the value in 80v-450v

lp-industry

WhatsApp 商业帐号



郑州蓝普实业有限公司

Zhengzhou LP Industry CO., LTD.

Phone: 0086-19337889070

Web: <https://lpwindingwire.com>

Email: office@cnlpzz.com

Add: NO. 86 Jingsan Road, Jinshui District, Zhengzhou, China